

A WORLD OF SOLUTIONS

AGENCY CERTIFICATIONS



SMART SOLUTIONS FOR THE LABELING INDUSTRY

UNWINDER & REWINDER FOR EPSON TM-C3500 PRINTER



LABEL REWINDER (ASD1111-S0) - Epson TM-C3500 printer - LABEL UNWINDER (ASS1111-S0)
(Not included)

The unwinder and rewinder for Epson TM-C3500 printers are used to manage rolls of media up to 5", while having an outside diameter up to 10". Units are equipped with adjustable core holder from 1.57" up to 4.64".

To guarantee an aligned media path in the system, the printer plate is available to connect the rewinder and unwinder together. It also offers a customized sliding support where lean and fix the Epson printer.

An external power supply 100/240VAC - 2.5A $\overline{\text{---}}$ at 24V allows an electronic circuit to provide, through the tension arm, the adjustment of the rotation speed and rotation direction. A 2A fuse is used as protection.

The unwinder and rewinder for the Epson TM-C3500 printers have two types of speed adjustments: it is possible to set the main speed through a knob and the tension arm automatically adjusts the speed from zero, up to the desired speed. When the roll runs out, each device stops beeping.

LABEL UNWINDER

The position of the tension arm is calibrated as follows:


- When the printer forwards the media for printing, the tension arm goes up, the device unwinds the media.
- When the tension arm is in the middle position, the device is idle.
- When the printer pulls back the media, the tension arm goes down, the device rewinds it.

LABEL REWINDER

The position of the tension arm is calibrated as follows:

- When the printer forwards the media for printing, the tension arm goes down, the device rewinds the media.
- When the tension arm is in the middle position, the device is idle.
- When the printer pulls back the media, the tension arm goes up, the device unwinds it.

| LABEL UNWINDER | |
|----------------|---|
| ASS1111-S0 | from 1.57" up to 3" adjustable core holder |
| LABEL REWINDER | |
| ASD1111-S0 | from 1.57" up to 3" adjustable core holder |
| PRINTER PLATE | |
| EPS35-JPL | UW&RW printer plate for EPSON TM-C3500 |



SMART SOLUTIONS FOR THE LABELING INDUSTRY

UNWINDER & REWINDER FOR EPSON C7500 PRINTER

The unwinder and rewriter for Epson C7500 printers are used to manage rolls of media up to 5", while having an outside diameter up to 10" (250mm). Units are equipped with adjustable core holder from 1.57" up to 4.64" (40-118mm).

The printer feet should fit into notches on the printer plate. This way the correct unwinding / rewinding operations are guaranteed and units are safely connected to the printer.

An external power supply 100/240VAC - 2.5A $\overline{\text{---}}$ at 24V allows an electronic circuit to provide, through the tension arm, the adjustment of the rotation speed and rotation direction. A 2A fuse is used as protection.



LABEL REWINDER (ASD1111-S0) - Epson C7500 printer - LABEL UNWINDER (ASS1111-S0)
(Not included)

The unwinder and rewriter for the Epson C7500 printers have two types of speed adjustments: it is possible to set the main speed through a knob and the tension arm automatically adjusts the speed from zero, up to the desired speed. When the roll runs out, each device stops beeping.



LABEL UNWINDER

The position of the tension arm is calibrated as follows:

- When the printer forwards the media for printing, the tension arm goes up, the device unwinds the media.
- When the tension arm is in the middle position, the device is idle.
- When the printer pulls back the media, the tension arm goes down, the device rewinds it.



LABEL REWINDER

The position of the tension arm is calibrated as follows:

- When the printer forwards the media for printing, the tension arm goes down, the device rewinds the media.
- When the tension arm is in the middle position, the device is idle.
- When the printer pulls back the media, the tension arm goes up, the device unwinds it.

LABEL UNWINDER

ASS1111-S0

from 1.57" up to 4.64" adjustable core holder

LABEL REWINDER

ASD1111-S0

from 1.57" up to 4.64" adjustable core holder